

1-3/8" Ø X 14 GA. SERIES

- Capacity : Up to 80 lbs. (See chart below)
- Minimum B.F.R. : 4"
- Maximum B.F.R. : 39" (Contact Sales if larger B.F.R. required).
- Bearings : Non-replaceable
- Construction : Formed end bearing retention.
- Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

STEEL ROLLER



- a**
TUBE
- Code Description
 - 1A 1-3/8" Ø x 14 Ga. Natural Finish (STD.)
 - 1F 1-3/8" Ø x 14 Ga. Zinc Plated
 - 1L 1-3/8" Ø x 14 Ga. Aluminium

- b**
BEARING
- Code Description
 - 10 Plain Ball BG-10 (STD.)

- c**
AXLE
- Code Description
 - 4N 5/16" Hex, Spring Loaded, Natural Finish (STD.)
 - 4T 5/16" Hex, Cottered, Natural Finish
 - 4Y 5/16" Hex, D+T 10-32 UNF, Natural Finish
 - 5D 5/16" Hex, Spring Loaded, Zinc Plated
 - 5J 5/16" Hex, Cottered, Zinc Plated
 - 5P 5/16" Hex, D+T 10-32 UNF, Zinc Plated

d
BETWEEN FRAME RAIL (B.F.R.)
Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

| B.F.R. (Inches) | 4 | 9 | 12 | 15 | 18 | 21 | 24 | 27 | 30 | 33 | 36 | 39 |
|-----------------------|----|----|----|----|----|----|----|----|----|----|----|----|
| Steel Roller Capacity | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 |

The Unit Handling Specialists

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9
T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership