

3-1/2" ϕ X 0.300 WALL SERIES

- Capacity : Up to 2,500 lbs. (See chart below)
- Minimum B.F.R. : 4"
- Maximum B.F.R. : 120" (Contact Sales if larger B.F.R. required).
- Bearings : Replaceable
- Construction : Press fit bearing retention
- Restrictions : All B.F.R. s require a cottered axle.



For more information on roller options or to place an order, contact our Order Desk!

STEEL ROLLER



- a**
TUBE
- | | |
|------|---|
| Code | Description |
| W0 | 3-1/2" ϕ x 0.300 Wall Natural Finish. (STD.) |
| W5 | 3-1/2" ϕ x 0.300 Wall Zinc Plated |

- c**
AXLE
- | | |
|------|--|
| Code | Description |
| QW | 1-1/16" Hex, Cotteded, Natural Finish (STD.) |

- b**
BEARING
- | | |
|------|-------------------------------------|
| Code | Description |
| 85 | Grease Packed BG-85 (STD.) |
| 90 | Precision BG-90 c/w insert |
| 95 | Dust Resistant BG-95 c/w Shot Guard |

d
BETWEEN FRAME RAIL (B.F.R.)
Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (inches)	4	9	15	21	27	33	39	45	51	57	63
Steel Roller Capacity #	2500	2500	2500	2500	2500	2500	2500	2500	2446	2441	2233

B.F.R. (inches)	69	75	81	87	93	99	105	111	117	120
Steel Roller Capacity #	2022	1845	1694	1564	1451	1351	1262	1030	775	648

*Interpolate for intermediate B.F.R.'s

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9
T:(905) 713-1377 F: (905) 713-0676 1-800-265-3094 www.almac.com

Almac
Industrial Systems

Quality Service Innovation Value Partnership

The Unit Handling Specialists