


1-5/8" Ø X 16 GA. SERIES

- Capacity : Up to 310 lbs. (See chart below)
- Minimum B.F.R. : 2"
- Maximum B.F.R. : 60" (Contact Sales if larger B.F.R. required).
- Bearings : Replaceable
- Construction : Press fit bearing retention.
- Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

STEEL ROLLER



a TUBE

- Code Description
- 6S 1-5/8"Ø x 16 Ga. Natural Finish (STD.)
- 6Y 1-5/8"Ø x 16 Ga. Zinc Plated

b BEARING

- Code Description
- 20 Grease Packed BG-20 (STD.)
- 25 High Speed & Quiet BG-25
- 45 High Capacity Grease Packed BG-45

c AXLE

- Code Description
- 8W 7/16"Hex, Spring Loaded, Natural Finish (STD.)
- 9B 7/16"Hex, Cottered, Natural Finish
- 9G 7/16"Hex, D+T 5/16-18UNC, Natural Finish
- 9M 7/16"Hex, Spring Loaded, Zinc Plated
- 9S 7/16"Hex, Cottered, Zinc Plated
- 9X 7/16"Hex, D+T 5/16-18UNC, Zinc Plated

d BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (inches)	6	9	15	21	27	33	39	45	51	57	60
Steel Roller Capacity	310	310	310	310	290	234	196	168	146	129	122

*Interpolate for intermediate B.F.R.'s

The Unit Handling Specialists

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9
T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership