


# 1.9" $\phi$ X 12 GA. SERIES


Capacity : Up to 260 lbs. (See chart below)  
 Minimum B.F.R. : 4"  
 Maximum B.F.R. : 63" (Contact Sales if larger B.F.R. required).  
 Bearings : Non-Replaceable  
 Construction : Formed end bearing retention.  
 Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

**STEEL ROLLER**

The Unit Handling Specialists



**a**  
TUBE

Code	Description
AA	1.9" $\phi$ x 12 Ga. Natural Finish (STD.)
AF	1.9" $\phi$ x 12 Ga. Zinc Plated

**b**  
BEARING

Code	Description
42	Grease Packed BG-42 (STD.)

**c**  
AXLE

Code	Description
8W	7/16" Hex, Spring Loaded, Natural Finish (STD.)
9B	7/16" Hex, Cottered, Natural Finish
9G	7/16" Hex, D+T 5/16-18UNC, Natural Finish
9M	7/16" Hex, Spring Loaded, Zinc Plated
9S	7/16" Hex, Cottered, Zinc Plated
9X	7/16" Hex, D+T 5/16-18UNC, Zinc Plated

**d**  
BETWEEN FRAME RAIL (B.F.R.)  
 Measurement between the inside of the two frame rails  
 Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (inches)	4	9	15	21	27	33	39	45	51	57	63
Steel Roller Capacity	260	260	260	260	243	204	164	141	125	108	94

\*Interpolate for intermediate B.F.R.'s

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9  
 T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership