


# 1.9" $\phi$ X 9 GA. SERIES

Capacity	: Up to 310 lbs. (See chart below)
Minimum B.F.R.	: 4"
Maximum B.F.R.	: 63" (Contact Sales if larger B.F.R. required).
Bearings	: Replaceable
Construction	: Press fit bearing retention.
Restrictions	: Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

**STEEL ROLLER**

The Unit Handling Specialists



- |  |  |
|--|--|
| <p><b>a</b><br/>TUBE</p> <p>Code Description</p> <p>EA 1.9" <math>\phi</math> x 9 Ga. Natural Finish (STD.)</p> <p>EF 1.9" <math>\phi</math> x 9 Ga. Zinc Plated</p> <p>9C 1.9" <math>\phi</math> x 0.2 Wall TK PVC Pipe</p>                                 | <p><b>c</b><br/>AXLE</p> <p>Code Description</p> <p>8W 7/16" Hex, Spring Loaded, Natural Finish (STD.)</p> <p>9B 7/16" Hex, Cottered, Natural Finish</p> <p>9G 7/16" Hex, D+T 5/16-18UNC, Natural Finish</p> <p>9M 7/16" Hex, Spring Loaded, Zinc Plated</p> <p>9S 7/16" Hex, Cottered, Zinc Plated</p> <p>9X 7/16" Hex, D+T 5/16-18UNC, Zinc Plated</p> |
| <p><b>b</b><br/>BEARING</p> <p>Code Description</p> <p>20 Grease Packed BG-20 (STD.)</p> <p>25 High Speed &amp; Quiet BG-25</p> <p>37 FR - 1625 - 7HDS, Miller</p> <p>45 High Capacity Grease Packed BG-45</p> <p>47 Dust Resistant BG-47 c/w Shot Guard</p> | <p><b>d</b><br/>BETWEEN FRAME RAIL (B.F.R.)</p> <p>Measurement between the inside of the two frame rails<br/>Eg. For a 14-1/4" B.F.R. measurement, enter 014.250</p>   |

B.F.R. (inches)	4	9	15	21	27	33	39	45	51	57	63
Steel Roller Capacity #	310	310	310	305	287	230	191	162	140	122	108

\*Interpolate for intermediate B.F.R.'s

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9  
 T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership