


# 2-1/2" $\phi$ X 14 GA. SERIES

- Capacity : Up to 310 lbs. (See chart below)
- Minimum B.F.R. : 5"
- Maximum B.F.R. : 60" (Contact Sales if larger B.F.R. required).
- Bearings : Replaceable
- Construction : Formed end housing retention c/w press fit bearing
- Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

## STEEL ROLLER



### a

#### TUBE

- Code Description
- KA 2-1/2"  $\phi$  x 14 Ga. Natural Finish (STD.)
- KF 2-1/2"  $\phi$  x 14 Ga. Zinc Plated

### b

#### BEARING

- Code Description
- 50 Grease Packed c/w housing BG-50 (STD.)
- 55 High Speed & Quiet c/w housing BG-55

### c

#### AXLE

- Code Description
- 8W 7/16" Hex, Spring Loaded, Natural Finish (STD.)
- 9B 7/16" Hex, Cottered, Natural Finish
- 9G 7/16" Hex, D+T 5/16 -18 UNC, Natural Finish
- 9M 7/16" Hex, Spring Loaded, Zinc Plated
- 9S 7/16" Hex, Cottered, Zinc Plated
- 9X 7/16" Hex, D+T 5/16-18 UNC, Zinc Plated

### d

#### BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails  
 Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (inches)	5	9	15	21	27	33	39	45	51	57	60
Steel Roller Capacity	310	310	310	310	262	211	175	149	129	113	106

\*Interpolate for intermediate B.F.R.'s

The Unit Handling Specialists

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9  
 T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership