


2-1/2" ϕ X 11 GA. SERIES

- Capacity : Up to 610 lbs. (See chart below)
- Minimum B.F.R. : 3"
- Maximum B.F.R. : 72" (Contact Sales if larger B.F.R. required).
- Bearings : Replaceable
- Construction : Press fit bearing retention
- Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

STEEL ROLLER



a

TUBE

- | | |
|------|--|
| Code | Description |
| PA | 2-1/2" ϕ x 11 Ga. Natural Finish (STD.) |
| PF | 2-1/2" ϕ x 11 Ga. Zinc Plated |

b

BEARING

- | | |
|------|---|
| Code | Description |
| 61 | Grease Packed (STD.) |
| 65 | Grease Sealed Pressure Lubricated BG-65 |
| 70 | Precision BG-70 |
| 67 | Dust Resistant BG-67 c/w Shot Guard |

c

AXLE

- | | |
|------|---|
| Code | Description |
| FA | 11/16" Hex, Spring Loaded, Natural Finish (STD.) |
| FF | 11/16" Hex, Cottered, Natural Finish |
| FL | 11/16" Hex, Drilled & Tapped (3/8-16 UNC), Natural Finish |
| FR | 11/16" Hex, Spring Loaded, Zinc Plated |
| FW | 11/16" Hex, Cottered, Zinc Plated |
| GB | 11/16" Hex, Drilled & Tapped (3/8-16 UNC), Zinc Plated. |

d

BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (Inches)	3	9	15	21	27	33	39	45	51	57	63	69	72
Steel Roller Capacity #	610	610	610	610	610	610	610	597	596	586	526	476	455

*Interpolate for intermediate B.F.R.'s

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9
T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com



Quality Service Innovation Value Partnership

The Unit Handling Specialists