

3" Ø X 11 GA. SERIES

- Capacity : Up to 310 lbs. (See chart below)
- Minimum B.F.R. : 4"
- Maximum B.F.R. : 60" (Contact Sales if larger B.F.R. required).
- Bearings : Replaceable
- Construction : Formed end housing retention c/w press fit bearing
- Restrictions : Rollers under 7" B.F.R. require a cottered axle.



For more information on further roller options or to place an order, contact our Order Desk!

STEEL ROLLER

The Unit Handling Specialists



a

TUBE
Code Description
TL 3" Ø x 11 Ga. Galvanized (STD.)

b

BEARING
Code Description
75 Grease Packed c/w housing BG-75 (STD.)

c

AXLE
Code Description
8W 7/16" Hex, Spring loaded, Natural Finish (STD.)
9B 7/16" Hex, Cottered, Natural Finish
9G 7/16" Hex, Drilled & Tapped (5/16-18 UNC), Natural Finish
9M 7/16" Hex, Spring Loaded, Zinc Plated
9S 7/16" Hex, Cottered, Zinc Plated
9X 7/16" Hex, Drilled & Tapped (5/16-18 UNC), Zinc Plated.

d

BETWEEN FRAME RAIL (B.F.R.)

Measurement between the inside of the two frame rails
Eg. For a 14-1/4" B.F.R. measurement, enter 014.250

B.F.R. (Inches)	4	9	15	21	27	33	39	45	51	57	60
Steel Roller Capacity #	310	310	310	310	262	211	175	149	129	113	106

*Interpolate for intermediate B.F.R.'s

155 Engelhard Drive, PO Box 730, Aurora, Ontario, Canada L4G 4J9
T:(905) 713-1377 F:(905) 713-0676 1-800-265-3094 www.almac.com

Almac
Industrial Systems

Quality Service Innovation Value Partnership